



**PRECISION PIN FEED**

Assures accurate forms registration and handling of challenging media

**RUGGED DESIGN**

For high production, large capacity paper supply and output stacking

**PRINTNET ENTERPRISE**

Provides remote configuration and management

**PRINTRONIX SYSTEM ARCHITECTURE (PSA2)**

Compatible with existing applications

**TOWER INTEGRATED IPDS SOLUTION**

Meets IBM AFP requirements

**POWER FOR DEMANDING APPLICATIONS**

The L1524 are rugged, high-speed printers specially built for demanding applications found in supply chains, industrial distribution centers, service bureaus and ERP environments. These printers combine laser quality and speed with the convenience and functionality of continuous forms printing.

**LASERLINE L1524**

The powerhouse LaserLine L1524 is the perfect printer for the budget conscious. Ideal for mailing labels, billing statements, bar code labels and more. The L1524 can handle forms up to 10" wide and uses heat and pressure to perfectly print your image. Its small footprint and compact size is perfect for office desktop or distributed workgroup. Or, place it in the optional power stacker for maximum functionality. The L1524 is rated at 24 pages per minute and a workload of 50,000 pages per month. Its PSA2 architecture means it is completely compatible with existing line matrix or thermal applications.

**THE L1524 HANDLES A WIDE VARIETY OF MEDIA**

- Labels for mailing and publishing
- Drum labels for chemicals
- Apparel shipping labels and hang tags
- Grocery store shelf labels
- Compliance labels for major appliances
- Customer statements and bills
- Medical laboratory bar codes



**SPEED**

Pages-Letter Portrait	24 ppm
Lines Speed	1584 lpm @ 6 LPI
Plot Speed	4.40 ips

**FIRST PAGE SPEED**

From Standby	<90 seconds
--------------	-------------

**TECHNOLOGY**

Imaging	Laser
Fusing	Heat and pressure
Drum Type	OPC
Paper Path	Straight through

**RESOLUTION**

Standard	300 x 300 dpi
----------	---------------

**WORKLOAD**

Monthly Workload	50,000 pages (8.5" x 11" portrait)
------------------	------------------------------------

**REPLACEMENT INTERVALS\***

Toner	8,000 pages @ 5% coverage
OPC Cartridge	30,000 pages
Developer Kit	100,000 pages
Fuser Roller Kit	300,000 pages

\*All items are end user replaceable

**MEDIA TYPES**

Type	Pin fed continuous plain paper, label stock, card stock and tag stock
Weight	18 lbs to 42 lbs bond Up to 100 lbs card and label stock
Thickness	0.014" max
Width	4.0" min to 10.0" max
Length	1" min to 99" max

**PRINTABLE AREA**

Print Width	8.25"
Print Height	Up to full form length - no margin required

**INTERFACES**

Standard	RS-232/ RS-422; IEEE 1284/Centronics parallel, diagnostic port
Optional	PrintNet Enterprise 10/100 Base T, Dataproducts parallel
CT Optional	Coax/Twinax with active parallel
Twinax	Integrated twinax interface for attachment to IBM Systems 36/38 and AS/400 directly or via IBM 5394 or 5494 workstation controller
Coax	Integrated coax interface for attachment to IBM 3174, 3274, or 3276 cluster controller
Switching	Auto switching between active ports

**SYSTEM CONNECTIVITY**

Emulation	Line Printer Plus PCL5 PGL/VGL (optional) 4028 IPDS (optional)
Drivers	Windows 2000/NT/XP

**PRINTER FEATURES**

Optional	Power assist stacker
----------	----------------------

**POWER**

Consumption	800 W – printing 42 W – stand by
Line voltage	100 – 120VAC (standard) 200 – 240 VAC (optional)
Line frequency	50/60 Hz

**ENVIRONMENTAL**

Operating Temperature	41° – 95° F
Operating Humidity	20 – 85% relative humidity
Maximum Altitude	7500 feet
Acoustic Noise	55 dBA

**DIMENSIONS**

	Printer	With Power Assist
Height	9.8"	39.5"
Width	18.2"	20.3"
Depth	19.3"	32.5"
Shipping Weight	55 lbs	64 lbs*

\* Option only - Shipping weight does not include printer

**GENUINE PRINTRONIX SUPPLIES**

Choosing the right supplies is critical for life of the printer, print quality, image durability and total cost of operation. Protect your investment with Genuine Printronix Supplies. The Printronix support staff has all the technical expertise, resources and familiarity with these supplies to help keep your mission critical applications flowing.

**GENUINE  
PRINTRONIX  
SUPPLIES**



EPA POLLUTION PREVENTER

© 2006 Printronix, Inc. All rights reserved. Printronix, ThernaLine, PrintNet, PSA, LaserLine, PGL, IGP, T5000e, T5000r, SmartLine, RFID Smart, SDLK, SLP, SLPP, SLPA, ODV, ODV Data Manager, SMT, 5r, SL5000e, SL5000r, SLPA7000r and P7000 are trademarks or registered trademarks of Printronix, Inc. All other trademarks, product names, and company names or logos herein, are the property of their respective owners. Printronix, Inc. utilizes "green" packaging for optimal recycling. Product appearance and/or specifications are subject to change without notice. PTX-159 (9/06)

14600 Myford Road, Irvine, CA 92606  
800-665-6210 • www.printronix.com

**PRINTRONIX**  
GLOBAL PRINTING...ENABLED.



**RUGGED DESIGN**

For high production, large capacity paper supply and output stacking

**PRECISION PIN FEED**

Assures accurate forms registration and handling of challenging media

**PRINTNET ENTERPRISE**

Provides remote configuration and management

**PRINTRONIX SYSTEM ARCHITECTURE (PSA2)**

Compatible with existing applications

**TOWER INTEGRATED IPDS SOLUTION**

Meets IBM AFP requirements

**VERSATILITY FOR DEMANDING APPLICATIONS**

The L5535 are rugged, high-speed printers specially built for demanding applications found in supply chains, industrial distribution centers, service bureaus and ERP environments. These printers combine laser quality and speed with the convenience and functionality of continuous forms printing.

**FLASHFUSION**

The L5535 printers feature FlashFusion technology. This innovative system uses high intensity light to fuse the image onto the media. The cool process completely eliminates the heat and pressure of traditional laser fusing systems. The result is a printer that doesn't require expensive "laser friendly" adhesives, and is capable of printing on difficult media like plastic cards or synthetic materials.

By combining the reliability of continuous forms printing and the flexibility of FlashFusion, this printer becomes the ideal product for challenging high volume print applications. The L5535 is rated at 35 pages per minute and a workload of 300,000 pages per month. Its PSA2 architecture means it is completely compatible with existing line matrix or thermal applications, providing a seamless migration path for users looking for higher performance. It can handle forms from 7" to 17.5" wide.

**THE L5535 HANDLES A WIDE VARIETY OF MEDIA:**

- Labels for mailing and publishing
- Drum labels for chemicals
- Plastic membership cards
- Apparel shipping labels and hang tags
- Grocery store shelf labels
- Compliance labels for major appliances
- Customer statements and bills
- Automobile window stickers
- Medical laboratory bar codes
- Tyvek law labels



**SPEED**

Pages-Letter Landscape	35 ppm
Pages-Letter Portrait	27 ppm
Lines Speed	1782 lpm @ 6 LPI
Plot Speed	4.95 ips

**FIRST PAGE SPEED**

From Standby	<60 seconds
--------------	-------------

**TECHNOLOGY**

Imaging	LED
Fusing	Flash Fusion
Drum Type	Selenium
Paper Path	Straight through

**RESOLUTION**

Standard	300 x 300 dpi
	240 x 240 dpi (optional)
	400 x 400 dpi (optional)

**WORKLOAD**

Monthly Workload	300,000 pages (8.5" x 11" landscape)
------------------	--------------------------------------

**REPLACEMENT INTERVALS\***

Toner	21,000 pages @ 4% coverage
Waste Toner Container	150,000 pages
Developer Mix	150,000 pages
Drum Kit	300,000 pages
Developer Unit	600,000 pages

\*All items are end user replaceable

**MEDIA TYPES**

Type	Pin fed continuous plain paper, label stock, card stock, tag stock, synthetics, plastic cards
Weight	17 lbs to 44 lbs bond Up to 125 lbs card and label stock
Thickness	0.014" max
Width	7.0" min to 16.0" max 17.5" max (optional)
Length	1" min to 99" max

**PRINTABLE AREA**

Print Width	14.6"
Print Height	Up to .66" full form length +/- .33" from perforation

**INTERFACES**

Standard	RS-232/ RS-422; IEEE 1284/Centronics parallel, diagnostic port
Optional	PrintNet Enterprise 10/100 Base T, Dataproducts parallel
CT Optional	Coax/Twinax with active parallel
Twinax	Integrated twinax interface for attachment to IBM Systems 36/38 and AS/400 directly or via IBM 5394 or 5494 workstation controller
Coax	Integrated coax interface for attachment to IBM 3174, 3274, or 3276 cluster controller
Switching	Auto switching between active ports

**SYSTEM CONNECTIVITY**

Emulation	Line Printer Plus PCL5 PGL/VGL (optional) 4028 IPDS (optional)
Drivers	Windows 2000/NT/XP

**PRINTER FEATURES**

Optional	Cut sheet feeder
----------	------------------

**POWER**

Consumption	4.3 kW – printing 500 W – stand by
Line voltage	200 – 240 VAC
Line frequency	50/60 Hz

**ENVIRONMENTAL**

Operating Temperature	50° – 86° F
Operating Humidity	30 – 80% relative humidity
Maximum Altitude	7500 feet
Acoustic Noise	60 dBA

**DIMENSIONS**

	Printer
Height	47.5"
Width	50.6"
Depth	36.8"
Shipping Weight	500 lbs

**GENUINE PRINTRONIX SUPPLIES**

Choosing the right supplies is critical for life of the printer, print quality, image durability and total cost of operation. Protect your investment with Genuine Printronix Supplies. The Printronix support staff has all the technical expertise, resources and familiarity with these supplies to help keep your mission critical applications flowing.

**GENUINE  
PRINTRONIX  
SUPPLIES**



**RUGGED DESIGN**

400,000 page per month duty cycle

**HIGH SPEED**

32 pages per minute

**EASE OF USE**

Fast supply item replacement

**WIDE RANGE OF OPTIONS**

Cabinet stand, power assist stacker, full power stacker, cutter, MICR

**NO FORMS WASTE**

Leading edge self alignment, reversible drive system

**DESIGNED FOR MISSION CRITICAL APPLICATIONS**

Printronix, the world leader in continuous form laser printers, offers global reach in sales, support and logistics that meets the needs of customers regardless of company size or geographic location. Extending this leadership further is the L7032. This printer delivers a powerful combination of speed, ease of use, small foot print, high workload, flexible media handling and affordability. Rated at 32 pages per minute and up to 400,000 pages per month, this printer is ideal for use in distribution, supply chain and manufacturing applications.

**MAXIMUM UPTIME – MINIMUM HASSLE**

Designed specifically for high volume mission critical applications, each consumable or service item delivers extended life to minimize the number of user interventions. When items do need refreshing, they can be replaced in minutes without tools or special training. This long life coupled with extreme ease of use creates a print solution that reliably delivers high volume throughput.

**CONTINUOUS FORMS ADVANTAGE**

The L7032 offers laser printing's high quality imaging with the ability to handle challenging forms not possible with cut sheet feeders. A straight paper path and positive engagement tractor drive system ensures that heavy card stock, labels, tags or massive print jobs run jam and misalignment free. In addition, continuous forms printing offers the advantage of handling very large input and output, while naturally keeping forms together and in sequence.



**SPEED**

Pages-Letter Landscape	32 ppm
Pages-Letter Portrait	25 ppm
Lines Speed	1650 lpm @ 6 LPI
Plot Speed	4.58 ips

**MEMORY**

Standard	12MB RAM
	16MB Flash

**FIRST PAGE SPEED**

Initial From Power Up	<200 seconds
From Standby	<45 seconds
Ready State	<20 seconds

**TECHNOLOGY**

Imaging	Laser
Fusing	Heat and pressure
Drum Type	OPC
Paper Path	Straight through

**RESOLUTION**

Standard	600 x 600 dpi
Software Selectable	300 x 300 dpi

**WORKLOAD**

Monthly Workload	400,000 pages (8.5" x 11" landscape)
Maximum Total Pages	24,000,000 pages (8.5" x 11" landscape)
Design Life	5 years

**REPLACEMENT INTERVALS\***

Toner	32,000 pages @ 4% coverage
Waste Toner Container	64,000 pages
Felt Wiper	64,000 pages
OPC Cartridge	400,000 pages
Developer Unit	800,000 pages
Fuser Unit	800,000 pages

\*All items are end user replaceable

**MEDIA TYPES**

Type	Pin fed continuous plain paper, label stock, card stock and tag stock
Weight	16 lbs to 42 lbs bond 33-116 lbs index 36 – 129 tag & label
Thickness	0.014" max
Width	15.25" maximum edge-to-edge 5.9" minimum hole-to-hole
Length	3" min to 33" max

**PRINTABLE AREA**

Print Width	13.6"
Print Height	Up to full form length - no margin required

**INTERFACES**

Parallel	IEEE-1284 (standard)
Ethernet	10/100 Base T (standard)

**SYSTEM CONNECTIVITY**

Emulation	PCL5e (standard) PGL (optional) VGL (optional)
Drivers	Windows 2000/NT/XP/VISTA

**PRINTER FEATURES**

Optional	Cabinet stand Power assist stacker Full power stacker Cutter MICR toner
----------	---

**POWER**

Consumption	1.3 kW – printing 700 W – during printing 70 W – standby mode
Line voltage (+/- 10%)	100 – 120 VAC (standard) 200 – 240 VAC (optional)
Line frequency	50/60 Hz

**ENVIRONMENTAL**

Operating Temperature	50° – 90° F
Operating Humidity	20 – 80% Relative Humidity
Maximum Altitude	7,500 feet
Acoustic Noise	<55 dBA

**DIMENSIONS**

	Printer	W/ Cabinet	W/ Power Assist Stacker	W/ Full Power Stacker
Height	16.5"	48"	48"	46"
Width	24"	40"	63"	39"
Depth	24"	25"	25"	25"
Shipping Weight	134 lbs	50 lbs	65 lbs	133 lbs

Dimensions include the printer and option  
Weights are individual items

**GENUINE PRINTRONIX SUPPLIES**

Choosing the right supplies is critical for the life of the printer, print quality, image durability and total cost of operation. Protect your investment with Genuine Printronix Supplies. The Printronix support staff has all the technical expertise, resources and familiarity with these supplies to help keep your mission critical applications flowing.

